

LISTEC[®]

t e l e p r o m p t e r s

BTL-2015E 15" LED

*Enhanced replacement display
for Listec Studio Teleprompter*



- 2X looping BNC Composite Inputs with 75-Ohm termination switch
- 1X DB 15-Pin VGA Connector
- Remote Control for selection of all settings from easy-to-read menus Image
- Reversal by menu command
- Brightness: 1600 nits
- Contrast: 1000:1
- Resolution: SXGA 1280X1024
- Power inputs: 12VDC \pm 10% by means of external universal A/C Adapter
- Power draw: Under 55W at maximum brightness
- Backlight life: 45,000 hours
- Viewing angle: 170° horizontal
- Operating temperature: +32°F—122°F/0°C—+50°C
- TV Standard: NTSC/PAL/SECAM
- ROHS compliant

Listec **BTL-2015E** 15" LED Enhanced replacement display for Listec Studio Teleprompter. The display does not come with mounting hardware. This display can also be used for other manufactures 15" display. Mounting hardware for other manufactures, if needed, maybe supplied at additional cost.



The Tiffen Company
90 Oser Avenue, Hauppauge, NY 11788
1-800-645-2522 • 631-273-2500 • tiffen.com

Tiffen International Ltd.,
Pinewood Studios, Iver Heath, SLO ONH
el: +44(0870) 100 1220 • Fax +44(0)1753 652776

All Registered Trademarks are the property of their respective owners.
Prices and specifications subject to change without notice.

© 2014 The Tiffen Company. All rights reserved.